

## Portable Boiler Room 150 HP / 5,175 PPH

## RH-150

## **Features:**

- Boiler and Burner Package
- Control Systems and Panels
- Onboard Fuel Tank 1,000 Gallons
- Fuel Handling Equipment
- Feedwater Tank and Pump
- Water Softener with Chemical Tank and Pump
- Blowdown Separator

General Information	
Rental Category	Portable Boiler Room
Boiler Size	150 BHP
Max Output Capacity	5,175 PPH (2.4 T/H)
Max Pressure (MAWP)	150 PSIG (10.3 BARG)
Fuel(s)	Natural Gas / #2 Oil / Propane
Service	LPS / HPS / HHW
NOx Emission Rating	70 PPM

Connections	
Steam Outlet	6" 300# FLG
Stack Exhaust	16" Ø
HHW Supply	6" 150# FLG
HHW Return	6" 150# FLG
City Water	2" NPT
Condensate Return	2" NPT
Natural Gas	2" NPT
#2 Oil Supply	1" NPT
#2 Oil Return	1" NPT
Blowdown Drain	4" 150# FLG
System Drain	1 ¼" NPT
Electrical	2" NPT

Output Specifications		
<b>Operating Range</b>	10 – 140 PSIG (0.7 – 9.7 BARG)	
Turndown (NG/#2 Oil)	4.5:1 / 3.3:1	
Oil Tank Capacity	1,000 GAL (1,890 L)	
Steam Quality	99.5%	
Efficiency	80% - 83%	
HHW Design Flow	450 GPM@20°FΔT (1,700 LPM@11°CΔT)	

Dimensions	
Overall Length	40' (12.2 M)
Overall Width	08' (2.4 M)
Overall Height	13′ 06″ (4.1 M)
<b>Shipping Weight</b>	37,000 LBS (16,780 KGS)
Operating Weight	41,000 LBS (18,600 KGS)

Input Specifications	
City Water	20 GPM@50 PSIG (75 LPM@3.5 BARG)
Electricity	480 V / 3 PH / 60 Hz @ 40 A
Fuel Input (NG / #2 Oil)	6.3 MMBTU/hr (1.85 MW)
NG Flow	1,400 – 6,280 CFH (40 – 178 m³/hr)
NG Pressure	2 – 10 PSIG (0.14 – 0.69 BARG)
#2 Oil Flow	13.5 – 45 GPH (51 – 170 LPH)
#2 Oil Pressure	Use Onboard Oil Pump
Pilot	Propane Tank Included

Last updated on: 17-Dec-24

HPS: High Pressure Steam LPS: Low Pressure Steam HHW: Hydronic Hot Water DHW: Domestic Hot Water



