## Portable Boiler Room 250 HP / 8,625 PPH

## RH-250

## Features:

- Boiler and Burner Package
- Control Systems and Panels
- Onboard Fuel Tank 1,000 Gallons
- Fuel Handling Equipment
- Feedwater Tank and Pump
- Water Softener with Chemical Tank and Pump
- Blowdown Separator

<u> </u>		
General	Intori	mation
General		nation

Rental Category	Portable Boiler Room
Boiler Size	250 BHP
Max Output Capacity	8,625 PPH (2.4 T/H)
Max Pressure (MAWP)	250 PSIG (17.2 BARG)
Fuel(s)	Natural Gas / #2 Oil / Propane
Service	HPS / HHW
NOx Emission Rating	60 PPM

Connections	
Steam Outlet	6" 300# FLG
Stack Exhaust	16" Ø
HHW Supply	6" 150# FLG
HHW Return	6" 150# FLG
City Water	2" NPT
Condensate Return	2" NPT
Natural Gas	2″ NPT
#2 Oil Supply	¾″ NPT
#2 Oil Return	¾″ NPT
Blowdown Drain	4" 150# FLG
System Drain	1 ½" NPT
Electrical	2" NPT

Atlas Copco

Rental

Output Specifications		
Operating Range	15 – 235 PSIG (1 – 16.2 BARG)	
Turndown (NG/#2 Oil)	10:1/8:1	
Oil Tank Capacity	1,000 GAL (1,890 L)	
Steam Quality	99.5%	
Efficiency	80% - 83% / 84% - 87%	
HHW Design Flow	870 GPM@20°FΔT (3,300 LPM@11°CΔT)	

Dimensions	
Overall Length	40' (12.2 M)
Overall Width	08' (2.4 M)
Overall Height	13' 06" (4.1 M)
Shipping Weight	47,400 LBS (21,500 KGS)
Operating Weight	56,100 LBS (25,450 KGS)

Input Specifications	
City Water	30 GPM@50 PSIG (114 LPM@3.5 BARG)
Electricity	480 V / 3 PH / 60 Hz @ 90 A
Fuel Input (NG / #2 Oil)	9.9 MMBTU/hr (2.9 MW)
NG Flow	990 – 9,900 CFH (40 – 178 m³/hr)
NG Pressure	3 – 10 PSIG (0.2 – 0.7 BARG)
#2 Oil Flow	8.7 – 69.4 GPH (33 – 263 LPH)
#2 Oil Pressure	Use Onboard Oil Pump
Pilot	Propane Tank Included

Last updated on: 12-Feb-25

Atlas Copco

HPS: High Pressure Steam LPS: Low Pressure Steam HHW: Hydronic Hot Water DHW: Domestic Hot Water

Atlas Copco Rental www.atlascopcorental.com

Subject to change without prior notice. Information is for guidance only. Please contact your nearest Rental office for detailed application advice.